

before Tues 5. says 0

The Mayor declared the Ordinance duly passed.

Strong moved that a Committee of Force be appointed in conjunction with the Clerk to consider the propriety or necessity of the purchase of a safe for the keeping of the town records & papers.

seconded by Gray and Carried.

The Mayor appointed Strong, Seck & Gray.

A Remonstrance of Citizens and Property owners on North Main Street was read, protesting against the putting down of walk along said Street and on motion of Strong seconded by Vincent was referred to Sidewalk Committee

On motion of Vincent seconded by Seck Council adjourned.

J. Brinkhemp
Clerk

Joseph Barnaby
Mayor.

Council Rooms Alliance

Monday eve. Jan 15. 1877

No Council meeting was held there being no Quorum.

J. Brinkhemp
Clerk.

Council Rooms Alliance

Monday evening Feb 5. 1877

Council convened in regular session Mayor Barnaby presiding.

Roll called, Members present: Seck, Vincent, Gray, Ellison & Strong absent. J. K. S.

Minutes of Special session read and approved.

Fire Dept Committee recommended

the immediate Repairing or Removing of the unoccupied Building standing on S. E. Corner of Arch + Grand Street belonging to W. N. Wallace as it now endangers the surrounding property.

On motion of Strong seconded by Vincent the Report of the Committee was accepted + the Clerk requested to notify the owner of said building to comply with the report of the Committee.

Reports of the members + officers belonging to Horse Companies No 1 + No 2, Hook + Ladder Co No 1. + Engine Co No 1. were read, + accepted upon motion of Gray seconded by Strong.

On motion of Vincent seconded by Leek the Fire Dept Committee were instructed to procure all articles now needed by the Fire Dept. Carried.

Street Committee through E. M. Gray reported that he settled with Mr Gastell in full upon the order drawn on last meeting. on motion of Strong seconded by Vincent, Report was accepted.

Strong moved that the Gas Committee meet with Mr King to morrow morning at 9 o'clock to arrange in regard to the burning of Gas + Coal in the office below. seconded by Leek + Carried.

The following was read:

Specifications for grading, curbing and paving the gutters of Albany Street from the C. & W. R.R. to the west side of Arch Street.

Grading

- 1st The entire surface of the Street shall be brought to the grade as established by ordinance.
- 2nd The gutters shall be excavated four feet in width
- 3rd twenty two inches below the surface of the gutter when reduced to grade.
- 3rd The earth taken from all excavations shall be used to make the fills in the Street, unless otherwise ordered by the "Street Committee" or

"City Engineer:

4. All excavations shall be estimated and paid for by the cubic yard. The extreme haul shall be twelve hundred feet, but if the Street Committee require a haul of greater distance, an additional cent per cubic yard shall be allowed for each additional hundred feet of distance.

Pile drain

A six inch tile drain shall be placed under the curb stone twenty seven inches below the lowest part of the gutter. The opening made to receive the tile shall be filled with good clean gravel

Foundation

for
Paving Stone

1st. Good coarse sand or gravel shall be placed in the bottom of said excavation for ditches, to the depth of at least twelve (12) inches and must be well fracked or "tamped" with a maul or "rammer" in the following manner, viz: when four inches shall have been deposited in the bottom of said excavation it must be well tamped, then one additional layer of about the same thickness, tamped in the same way until the whole amount is deposited, to be estimated and paid for by the cubic yard after the tamping is done.

Curb Stone.

The Curb Stone shall be five inches in thickness twenty inches deep and not less than thirty inches long. They shall be dressed on the front side or that side facing the street, at least half way down, and on the back side one fourth the way down. The ends shall be dressed so as to fit closely together, and the top so as to conform to the slope of the sidewalk. They shall be full throughout their entire length and depth. They shall be placed in perfect line and of proper elevation, as directed by the "City Engineer." They shall incline toward the sidewalk at an angle of about fifteen degrees. They shall be paid for by the linear foot, to be measured on the Street after the work is done.

Paving Stone.

The Stone for paving the gutters shall be from four to six inches wide, six to eight inches in length and ten inches deep. They shall be fit as closely together as possible and shall be laid to form as even a surface as possible. At the curbstones they shall be nine inches below the top of the curbstone, and at the outer edge six inches higher, forming an even slope from side to side, and each stone must rest solid on the bed of gravel below.

2^d The gutters across the Street and Alley Crossings, shall be paved wider than at any other points, as directed by the "Street Committee" They shall be slightly concave, so as not to obstruct the free and easy passage of vehicles across them.

3^d After the paving stone are laid, coarse sand shall be used in sufficient quantity to thoroughly fill all the joints and crevices.

4th The paving to be paid for by the square foot, the measurement to be made, after the work is completed.

Quality of Stone.

The Stone for both the paving and curbing, shall be in Quality, equal to the stone taken from the "Austin Flag-Stone Co.'s quarry near Warren Pumbull Co Ohio.

Supervision

The whole of the work and the quality of material used, shall be subject to the control and inspection of the "Street Committee" and "City Engineer" and must be approved by both before being accepted and paid.

On motion of Strong seconded by Vincent the Specifications as read were adopted and ordered filed together with the plans & profile.

On Motion of Strong seconded by Gray passed to 1st Reading "A Resolution declaring the necessity for Grading, Draining, Curbing and Paving Alliance Street between C. & P. R.R. and Arch Street.

Vincent moved that the Rules be suspended

